

FCBR_LOG (FINAL) 04.57124004.GPJ FUGRO DATA TEMPLATE 042610.GDT 11/12/13

DEPTH, FT	WATER LEVEL	SYMBOL	SAMPLES	BLOWS PER FOOT	LOCATION: Eads Avenue COORDINATES: N 30° 01' 00.5" W 90° 03' 00.9" SURFACE EL.: Not Available	STRATUM DEPTH, FT	CLASSIFICATION					SHEAR STRENGTH								
							UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT							
					STRATUM DESCRIPTION															
					ASPHALT , 5.5-inches															
1					BASE COURSE , 7.5-inches, sand and shells, tan	0.5														
2					POORLY GRADED SAND (SP) , tan, with clay pockets and shells	1.1		10												
4					- with clay seams and layers below 3.9'															
5					FAT CLAY (CH) , very soft to soft, tan, with ferrous staining	4.6	60	70	98	24	74	▼	□							
						5.3														

NOTES:

- Terms and symbols defined on Plates A-5a and A-5b.

COMPLETION DATE: February 20, 2013
 TOTAL DEPTH: 5.3'
 CAVED DEPTH: Not Applicable
 DRY AUGER: 0' to 5.3'
 WET ROTARY: Not Applicable
 BACKFILL: Sand/ Cold Patch Asphalt
 LOGGER: C. Brewer



Milneburg Street Improvements FEMA

LOG OF BORING NO. EADS-4

New Orleans, Louisiana

Project No.

04.57124004

PLATE A-4