

DEPTH, FT	WATER LEVEL	SYMBOL	SAMPLES	BLOWS PER FOOT	LOCATION: See Plate 1	STRATUM DEPTH, FT	CLASSIFICATION					SHEAR STRENGTH								
					COORDINATES: N 29° 58' 43.4" W 90° 06' 14.3"		UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT							
STRATUM DESCRIPTION																				
					ASPHALT, 2.8-inches	0.2														
					POORLY GRADED SAND WITH SILT (SP), medium-dense, tan															
1				N=9																
2																				
3				N=11				11	8											
4																				
5				N=14																
5.7						5.7														
6																				
7																				
8																				
9																				

NOTES:

1. Terms and symbols defined on Plates A-12a and A-12b.

COMPLETION DATE: October 2, 2013
 TOTAL DEPTH: 5.7'
 CAVED DEPTH: Not Applicable
 DRY AUGER: 0' to 5.7'
 WET ROTARY: Not Applicable
 BACKFILL: Sand/ Cold Patch Asphalt
 LOGGER: By Contractor



Fugro Consultants, Inc.

Mid City Street Improvements FEMA

LOG OF BORING NO. MC-06

New Orleans, Louisiana

Project No.

04.57124028

PLATE A-6