

FCBR_LOG (FINAL) 04.57124029.GPJ FUGRO DATA TEMPLATE 042610.GDT 01/31/14

DEPTH, FT	WATER LEVEL	SYMBOL SAMPLES	BLOWS PER FOOT	LOCATION: Cartier Drive COORDINATES: N 30° 01' 18.06" W 90° 04' 46.12" SURFACE EL.: Not Available	STRATUM DEPTH, FT	CLASSIFICATION					SHEAR STRENGTH							
						UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT						
				STRATUM DESCRIPTION														
				CONCRETE , 8.5-inches														
1			N=23	BASE COURSE , medium dense with sand	0.7													
2																		
3			N=18	POORLY GRADED SAND (SP) , medium-dense, brown	2.7		3	1										
4																		
5				- very dense below 4.7'														
6			N=42				4	6										
6.2					6.2													
7																		
8																		
9																		

NOTES:

1. Terms and symbols defined on Plates A-12a and A-12b.

COMPLETION DATE: September 16, 2013
 TOTAL DEPTH: 6.2'
 CAVED DEPTH: Not Applicable
 DRY AUGER: 0' to 6.2'
 WET ROTARY: Not Applicable
 BACKFILL: Sand/ Cold Patch Asphalt
 LOGGER: By Contractor



Fugro Consultants, Inc.

Lake Terrace and Lake Oaks Street Improvements FEMA

LOG OF BORING NO. LTO-03

New Orleans, Louisiana

Project No.

04.57124029

PLATE A-3