

DEPTH, FT	WATER LEVEL	SYMBOL SAMPLES	BLOWS PER FOOT	LOCATION: Lake Oaks Parkway COORDINATES: N 30° 01' 45.59" W 90° 03' 29.32" SURFACE EL.: Not Available	STRATUM DEPTH, FT	CLASSIFICATION					SHEAR STRENGTH								
						UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT							
				STRATUM DESCRIPTION															
				CONCRETE, 5.5-inches															
1			N=19	POORLY GRADED SAND (SP), medium-dense, with shells	0.5		10	9											
2				- with gravel below 2.5'															
3			N=20				12	7											
4				- with clay below 4.5'															
5			N=15																
6					6.0														

NOTES:

1. Terms and symbols defined on Plates A-12a and A-12b.

COMPLETION DATE: September 16, 2013
 TOTAL DEPTH: 6'
 CAVED DEPTH: Not Applicable
 DRY AUGER: 0' to 6'
 WET ROTARY: Not Applicable
 BACKFILL: Sand/ Cold Patch Asphalt
 LOGGER: By Contractor



Fugro Consultants, Inc.

Lake Terrace and Lake Oaks Street
Improvements FEMA

LOG OF BORING NO. LTO-10

New Orleans, Louisiana

Project No.

04.57124029

PLATE A-10