

DEPTH, FT	WATER LEVEL	SYMBOL SAMPLES	BLOWS PER FOOT	LOCATION: See Plate 1 COORDINATES: N 29° 57' 53.3" W 90° 05' 43.6" SURFACE EL.: Not Available	STRATUM DEPTH, FT	CLASSIFICATION					SHEAR STRENGTH							
						UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT						
				STRATUM DESCRIPTION														
				ASPHALT, 6-inches														
				CONCRETE, 5.5-inches	0.5													
1				FAT CLAY (CH), firm, gray - with sand, shell fragments and organics to 2'	1.0		49	62										
2				- with wood and organics from 2' to 4'														
3																		
4																		
5					5.0			58	82	19	63							
6																		
7																		
8																		
9																		

**NOTES:**

- Terms and symbols defined on Plates A-16a and A-16b.

COMPLETION DATE: October 2, 2013  
 TOTAL DEPTH: 5'  
 CAVED DEPTH: Not Applicable  
 DRY AUGER: 0' to 5'  
 WET ROTARY: Not Applicable  
 BACKFILL: Sand/ Cold Patch Asphalt  
 LOGGER: By Contractor



Fugro Consultants, Inc.

Mid City Street Improvements FEMA

**LOG OF BORING NO. MC-41**

New Orleans, Louisiana

Project No.

04.57124028

PLATE A-9