

FCBR_LOG (INPUT IN INCHES) 57124026.GPJ FUGRO DATA TEMPLATE 042610.GDT 07/01/13

DEPTH, FT	WATER LEVEL	SYMBOL SAMPLES	BLOWS PER FOOT	LOCATION: See Plate 1 COORDINATES: N 29° 58' 07" W 90° 02' 20" SURFACE EL.: Not Available	STRATUM DEPTH, FT	CLASSIFICATION					SHEAR STRENGTH								
						UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT							
				STRATUM DESCRIPTION															
				ASPHALT , 6-inches															
				FILL: BASE COURSE , 6-inches - Clay and shells, gray	0.5														
1				FAT CLAY (CH) , firm to stiff, gray - with shells at 1.0' - with gravel from 1.0' to 2.4'	1.0			25	64	21	43								
2				- with ferrous nodules below 2.4'															
5					5.3			47	86	25	61								

NOTES:

- Terms and symbols defined on Plates A-11a and A-11b.
- Water was not encountered during the dry auger drilling interval.

COMPLETION DATE: January 24, 2013
 TOTAL DEPTH: 5.3'
 CAVED DEPTH: Not Applicable
 DRY AUGER: 0' to 5.3'
 WET ROTARY: Not Applicable
 BACKFILL: Sand/Cold Patch Asphalt
 LOGGER: C. Brewer



Fugro Consultants, Inc.

St. Claude Paving Only FEMA

LOG OF BORING NO. B-69A

New Orleans, Louisiana

Project No.

04.57124026

PLATE A-6