						LOCATION: See Plate 1			CL/	ASSIF	SIFICATION			SHEAR STRENGTH						
, FI		WATER LEVE	SYMBOL SAMPLES		7 T	COORDINATES: N 29° 58' 12.4"	TOM H, FT	MΤ,	ō,%	%			Σ≘	☐ Penetrometer Unconfined ▼						
DEPTH, FT		TER	AMP		BLOWS PER FOOT	W 90° 02' 27.2" SURFACE EL.: Not Available	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, 9	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)							
		WA	Solo	ā		STRATUM DESCRIPTION	ا م ت	I E					7 2				ER SQ F			
_						ASPHALT, 2-inches	0.2							-	.5 1	.0 1	1.5 2.	.0 2	2.5	
-	-					FILL: GRANITE, 10.5-inches		-					-							
- - 1							1.0	-					_							
 	+		\bigotimes			FILL: Clay, firm, gray, with gravel and brick fragments	1.0	-					-							
-	-		\bigotimes					-					-							
- 2	-		\otimes					-					-							
-	-		\bigotimes			- with organics below 2.5'		-					-							
- - 3			\otimes					-					_							
-	-		\Rightarrow					-					-							
-	-		\otimes					-					-							
- 4	_					FAT CLAY (CH), soft, gray, with organics	3.9	-		64	101	27	- 74 -							
-	-							-			'0'	_,	-							
- 5	_							_ 56		68			_	. ▼						
-	-			_			5.3	<u></u> -					<u> </u>			<u> </u>			+-+	
F	-							-					-							
— 6 -	_												-							
-	-							-					-							
- 7	_							ļ.					_							
-	-							-					-							
-	-							-					_							
- 8 - 8								-					-							
70 TC	-							-					-							
610.GI	_							ļ.					_							
TE 042	-							-					-							
MPLA	-							-					-							
ATA TE	OTF	∟∟ ES:					1				COM	PLET	ION D	ATE:	Janu	ıary 2	25, 20°	13		
RO DA	NOTES: 1. Terms and symbols defined on Plates A-9a and A-9b.									TOTAL DEPTH: 5.3' CAVED DEPTH: Not Applicable										
J FUG	2	. ۷۷	ater v	was	not er	ncountered during the dry auger drilling interval.					DRY	AUGE	ER: 0'	to 5.3	3'					
26.GP	10.027									WET ROTARY: Not Applicable BACKFILL: Sand/Cold Patch Asphalt										
571240													C. Bre		0					
S) 04.																				
NCHË	_																			
NOTES: 1. Terms and symbols defined on Plates A-9a and A-9b. 2. Water was not encountered during the dry auger drilling interval. St. Claude Paving Only FEMA COMPLETION DATE: January 25 TOTAL DEPTH: 5.3' CAVED DEPTH: Not Applicable DRY AUGER: 0't o 5.3' WET ROTARY: Not Applicable BACKFILL: Sand/Cold Patch Asp LOGGER: C. Brewer St. Claude Paving Only FEMA LOG OF BORING NOTES: Fugro Consultants, Inc. New Orleans, Louisiana Project No. 04.57124026 PLA											O. I	B-5	8							
Ó Fu	ıgro	Co.	nsulta	nts	, Inc.	New Orleans, Louisiana			Project No. PL ATE							· ^	_2			
	. y, c	. 501	.curta		,	New Offeatis, Louisiaffa				04.57124026 PLATE A-3										