

# BORING LOG

**BORING NO.:** R3-P26 SCHINDLER DR.  
**PROJECT:** READ BLVD. IMPROVEMENTS  
**PROJECT LOCATION:** NEW ORLEANS, LA  
**BORING LOCATION:** SEE BORING LOCATION PLAN  
**BORING ELEVATION:** EXISTING GRADE  
**GEOL/ENGR:** RM  
**METHOD:** AUGER/ROTARY WASH DRILLING

**PROJECT NO.:** B12-084  
**DATE DRILLED:** 01/15/13  
**DATE COMPLETED:** 01/15/13  
**WATER LEVEL:** 7 ft  
**WATER LEVEL DATE:** 01/15/13  
**LOGGED BY:** WW  
**DRILLER:** DT

DEPTH (feet)	SAMPLE	Standard Penetration (Blows/Ft.)	Unconfined Compressive Strength (tsf)	Moisture Content (%)	Dry Unit Weight (pcf)	LL	PI	Symbol	MATERIAL CLASSIFICATION
0 - 1.5								[Concrete Symbol]	11.5" Concrete
1.5 - 3.5				19		36	19	[Gravel/Clay/Sand Symbol]	Intermix GRAVEL (G), Lean CLAY (CL), Silty Clayey SAND (SC-SM)
3.5 - 5.5		Wt of Hammer		30				[Clay Symbol]	Very Soft, Gray Sandy Lean CLAY with gravel and silt (CL)
5.5 - 7.5			0.25	32	86	34	14	[Sand/Clay Symbol]	Alternating layers of Silty SAND (ML) and Lean CLAY (CL)
7.5 - 10.0		10 b/ft <sup>5/5/5</sup>		30				[Silty Sand Symbol]	Gray SILTY SAND with clay lenses (SM)
10.0 - 10.5				25				[Loose Symbol]	---loose
10.5 - 20.0									Bottom @ 10'

**COMMENTS:**

-  AUGER
-  SPLIT SPOON
-  SHELBY TUBE