









BORING LOG

BORING NO.: R3-P31 GOOD DR.
PROJECT: READ BLVD. IMPROVEMENTS
PROJECT LOCATION: NEW ORLEANS, LA
BORING LOCATION: SEE BORING LOCATION PLAN
BORING ELEVATION: EXISTING GRADE
GEOL/ENGR: RM
METHOD: AUGER/ROTARY WASH DRILLING

PROJECT NO.: B12-084
DATE DRILLED: 01/15/13
DATE COMPLETED: 01/15/13
WATER LEVEL: 8 ft
WATER LEVEL DATE: 01/15/13
LOGGED BY: WW
DRILLER: DT

DEPTH (feet)	SAMPLE	Standard Penetration (Blows/Ft.)	Unconfined Compressive Strength (tsf)	Moisture Content (%)	Dry Unit Weight (pcf)	LL	PI	Symbol	MATERIAL CLASSIFICATION
									10" Concrete
			(1)	17					Gray fine SAND with silt, clay pockets and gravel (SM)
		27 b/ft ^{10/15/12}		20					Dense, Gray SILTY SAND (SM)
5			0.15	40	71	62	39		Very Soft, Gray Fat CLAY with silty sand pockets and organic pockets (CH)
		7 b/ft ^{4/3/4}		26					Loose, Gray SILTY SAND (SM)
		8 b/ft ^{3/4/4}		46					---loose, with clay pockets
10									
									Bottom @ 10' (1) 12.4% Passing #200 sieve
15									
20									

COMMENTS:

 AUGER
 SHELBY TUBE

 SPLIT SPOON