

FCBR_LOG (FINAL) 04.57144010.GPJ FUGRO DATA TEMPLATE 042610.GDT 2/9/15

DEPTH, FT	WATER LEVEL	SYMBOL SAMPLES	BLOWS PER FOOT	LOCATION: See Plate 1 COORDINATES: N 29° 55' 45.7" W 90° 06' 42.7" SURFACE EL.: Not Available	STRATUM DEPTH, FT	CLASSIFICATION					SHEAR STRENGTH					
						UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT				
				STRATUM DESCRIPTION							0.5	1.0	1.5	2.0	2.5	
				ASPHALT, 2 1/4-inches	0.2											
				CONCRETE, 7 5/8-inches												
1				LEAN CLAY (CL), gray, stiff	0.8											
2				- brown and gray from 2'												
3				FAT CLAY (CL), brown, stiff	3.0											
4																
5					5.0											
6																
7																
8																
9																

NOTES:

- Terms and symbols defined on Plates A-21a and A-21b.
- 5320 Dryades Street

COMPLETION DATE: December 2, 2014
 TOTAL DEPTH: 6'
 CAVED DEPTH: Not Applicable
 DRY AUGER: 2'
 WET ROTARY: Not Applicable
 BACKFILL: Sand/Cold patch asphalt
 LOGGER: Subcontractor to Fugro



Fugro Consultants, Inc.

Recovery Roads Project - Uptown and West
 Riverside

LOG OF BORING NO. C15

New Orleans, Louisiana

Project No.

04.57144010

PLATE A-15