

DEPTH, FT	WATER LEVEL	SYMBOL	SAMPLES	BLOWS PER FOOT	LOCATION: See Plate 1 COORDINATES: N 29° 55' 11.7" W 90° 06' 22" SURFACE EL.: Not Available	STRATUM DEPTH, FT	CLASSIFICATION						SHEAR STRENGTH				
					STRATUM DESCRIPTION		UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX (PI)	KIPS PER SQ FT				
					ASPHALT, 5 1/2-inches												
1					FAT CLAY (CH), gray, stiff to very stiff - with bricks to 1' - with shells to 2'	0.5			18	53	17	36					
2					- with reddish streaks to 4'												
3																	
4					- brown and gray from 4'			36	58	23	35						
5						5.0											
6																	
7																	
8																	
9																	

**NOTES:**

- Terms and symbols defined on Plates A-21a and A-21b.
- 820 Bordeaux Street

COMPLETION DATE: December 1, 2014  
TOTAL DEPTH: 6'  
CAVED DEPTH: Not Applicable  
DRY AUGER: 2'  
WET ROTARY: Not Applicable  
BACKFILL: Sand/Cold patch asphalt  
LOGGER: Subcontractor to Fugro



Fugro Consultants, Inc.

Recovery Roads Project - Uptown and West  
Riverside

**LOG OF BORING NO. C19**

New Orleans, Louisiana

Project No.

04.57144010

PLATE A-19