Page	1	of	1

BORING NO.: R16-P180 TANNER S. DAVIS DR.

PROJECT: READ BLVD IMPROVEMENTS

PROJECT: READ BLVD. IMPROVEMENTS **PROJECT LOCATION:** NEW ORLEANS, LA

BORING LOCATION: SEE BORING LOCATION PLAN

BORING ELEVATION: EXISTING GRADE

GEOL/ENGR: RM **METHOD:** AUGER

PROJECT NO.: B12-084

DATE DRILLED: 12/05/13

DATE COMPLETED: 12/05/13

WATER LEVEL: 6 ft

WATER LEVEL DATE: 12/05/13

LOGGED BY: WW

DRILLER: DT

IVIE	IHC	D: AUGE	(DRILLER: DI	
DEPTH (feet)	SAMPLE	Standard Penetration (Blows/Ft.)	Unconfined Compressive Strength (tsf)	Moisture Content (%)	Dry Unit Weight (pcf)	LL	PI	Symbol	MATERIAL CLASSIFICATION	
	В			15				A 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	6" of Concrete Tan Fine SAND with trace silt (SP-SM)	
		2b/ft ^{1/1/1}	(1)	19					Very Loose, Gray Silty SAND with shells (SM)	
- 5 - - <u>5</u> -	-		0.10	49	67				Very Soft, Gray and Black Fat CLAY (CH)	
- \(\sum_{\chi} \) -				32		59	40			
				57					brown with silt	
_ 10 _									Bottom at 10 Feet (1) % Passing #200 = 31.1%	
- 15 -										
- 20 -	COMMENTS:									
B BAG SPLIT SPOON SHELBY TUBE										