Depth (Feet) 40 Location: New Orleans, LA 35 -30 -25 = 20 -10 15 5 0 Project: FEMA Submerged Roads Program Client: City of New Orleans e - 70 H m s Seven Ward Neighborhood (Field Test) New Orleans, LA N/A N/A N/A SPT PP/ Strength Comp. Content Water 59.9 19.1 (%) Density (pcf) Wet 120 (%) Boring No. SW-5 90 PI (%) No. 200 Passing 17.7 (%) E 7 4 4 Boring completed at 5 feet below ground surface Coord.: 29° 59' 0.09" N; 90° 3' 41.89" W Dark gray CLAY (CH) with trace sand Tan and dark gray CLAYEY SAND (SC) 19" ASPHALT with CLAY base course Description of Stratum GSE&T File No.: 14-033 Technician: C.Thomas Rig Type: Trailer Driller: LTI Page: 1 of 1 Date: 5/8/2014

Sample Legend:

Core (Shelby Tube)
Standard Penetration (SPI)
No Recovery

Comments/Notes:
- Borehole backfilled per LA DOTD & LA DEQ requirements upon completion
- Dry Auger Depths = 0-5 ft.
- Ground water = Not encountered

ENGINEERING AND TESTING, INC. Geotechnical & Materials Consultants

SO

Auger Sample